



## XF-PTL11008-C

### Specification

Optical structure	Bi-Telecentric
Magnification	0.0727
Object field of view	Φ110.0mm
Image field of view	Φ8mm
Working Distance	250mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	115.9mm
F#	F5.5
Resolution	50.0μm
MTF	>0.3@185lp/mm
Distortion	<0.095%(0.127%)
Detector type:	

1/2'	6.4×4.8	88.0×66.0mm
1/2.3'	6.2×4.6	85.3×63.3mm
1/2.5'	5.8×4.3	79.8×59.1mm
1/3'	4.8×3.6	66.0×49.5mm

**XF-PTLAAABB-C/F/P/M- (L90E) - (VI)**

The fourth generation lens of Canrill

The camera mount (M & P mount need specify BFL)

Variable aperture option

Object FOV

90° Steering option

Image FOV

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL11008-C-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	
Modify2			Total:	
			Page:	Canrill OPTICS 

All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.